Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 05/09/2016 Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier Product Form: Mixture

Product Name: Natural Gas Compressed1.2. Intended Use of the Product

Use Of The Substance/Mixture: Fuel.

1.3. Name, Address, and Telephone of the Responsible Party

Manufacturer Supplier

Ferus Natural Gas Fuels, Inc.

NE 01-08-70-11W6M

Ferus Natural Gas Fuels
401-9th Ave SW Calgary

County of Grande Prairie #1, AB TOH 1JO Suite 1220

Alberta Canada T2P 3C5

1.4. Emergency Telephone Number Emergency Number : 877-923-3787

CanuTec 1-613-996-6666

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA classification

Simple Asphyant

Flam. Gas 1 H220 Compressed gas H280

Full text of hazard classes and H-statements: see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)





Signal Word (GHS-US/CA) : Danger

Hazard Statements (GHS-US/CA) : H220 - Extremely flammable gas.

H280 - Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary Statements (GHS-US/CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - In case of leakage, eliminate all ignition sources.

P403 - Store in a well-ventilated place.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Contact with gas escaping the container can cause frostbite.

2.4. Unknown Acute Toxicity No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification	
Methane	(CAS No) 74-82-8	>= 98	Simple Asphy	
			Flam. Gas 1, H220	

05/09/2016 EN (English US) 1/7

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

			Compressed gas, H280
Ethane	(CAS No) 74-84-0	0 - 1	Simple Asphy
			Flam. Gas 1, H220
			Liquefied gas, H280

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

Inhalation: Obtain medical attention if breathing difficulty persists. First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Contact with gas escaping the container can cause frostbite. Asphyxia by lack of oxygen: risk of death.

Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate.

Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Skin Contact: Contact with gas escaping the container can cause frostbite and freeze burns.

Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Do not extinguish burning gas if flow cannot be shut off immediately. Extinguish secondary FIRES with appropriate materials. Dry chemical, carbon dioxide, alcohol-resistant foam, water spray.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Extremely flammable gas.

Explosion Hazard: May form flammable/explosive vapor-air mixture. Container may explode in heat of fire.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Water vapor. Soot. Aldehydes. Ketones.

Other Information: Use water spray to disperse vapors.

05/09/2016 EN (English US) 2/7

^{*}Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Eliminate every possible source of ignition. Do not get in eyes, on skin, or on clothing. Do not breathe Gas.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Evacuate unnecessary personnel, isolate, and ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Stop leak, if possible without risk. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Check oxygen content before entering area. Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. Ruptured cylinders may rocket. Do not pressurize, cut, or weld containers. Asphyxiating gas at high concentrations.

Precautions for Safe Handling: Avoid prolonged contact with eyes, skin and clothing. Do not breathe gas.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed. **Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep in fireproof place. Cylinders should be stored firmly secured to prevent falling with valve protection cap in place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Storage Temperature: 50 °C 7.3. Specific End Use(s)

Fuel.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Methane (74-82-8)		
British Colombia	OEL TWA (ppm)	1000 ppm
Northwest Territories	OEL STEL (ppm)	1250 ppm
Northwest Territories	OEL TWA (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm

05/09/2016 EN (English US) 3/7

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Ethane (74-84-0)		
Alberta	OEL TWA (ppm)	1000 ppm
British Colombia	OEL TWA (ppm)	1000 ppm
Northwest Territories	OEL STEL (ppm)	1250 ppm
Northwest Territories	OEL TWA (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Gas detectors should be used when flammable gases or vapors may be released. Oxygen detectors should be used when asphyxiating gases may be released. Ensure all national/local regulations are observed.

Materials for Protective Clothing: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.











Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Hand Protection: Wear protective gloves. If material is cold, wear thermally resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation wear respiratory protection. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear a self-contained breathing apparatus (SCBA).

Thermal Hazard Protection: Wear thermally resistant protective clothing.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1.	Information o	n Basic Physica	I and Chemical	Properties
------	---------------	-----------------	----------------	------------

Physical State: GasAppearance: ColorlessOdor: OdorlessOdor Threshold: Not availablepH: Not availableEvaporation Rate: Not available

Melting Point : $-182.5 \, ^{\circ}\text{C} \, (-296.5 \, ^{\circ}\text{F})$

Freezing Point : Not available

Boiling Point : -161.6 °C (-258.88 °F) **Flash Point** : -188 °C (-306.4 °F)

Auto-ignition Temperature : 482 - 632 °C (899.6 - 1169.6 °F)

Decomposition Temperature : Not available

Flammability (solid, gas) : Extremely flammable gas

Vapor Pressure : Not available

Relative Vapor Density at 20°C : 0.5

Relative Density: Not availableSpecific Gravity: Not availableSolubility: Not available

05/09/2016 EN (English US) 4/7

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Partition Coefficient: N-Octanol/Water : Not available Viscosity : Not available

Explosive Properties : Contains gas under pressure; may explode if heated

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Hazardous reactions will not occur under normal conditions.

- 10.2. Chemical Stability: Contains gas under pressure; may explode if heated. May form flammable/explosive vapor-air mixture.
- 10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, open flames, sources of ignition and incompatible materials.
- **10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- **10.6.** Hazardous Decomposition Products: None known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified
Acute Toxicity (Dermal): Not classified
Acute Toxicity (Inhalation): Not classified
LD50 and LC50 Data: Not available
Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Symptoms/Injuries After Skin Contact: Contact with gas escaping the container can cause frostbite and freeze burns.

Symptoms/Injuries After Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Ethane (74-84-0)	
LC50 Inhalation Rat	658 mg/l/4h

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

12.2. Persistence and Degradability

Natural Gas Compressed	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Natural Gas Compressed	
Bioaccumulative Potential	Not established.

05/09/2016 EN (English US) 5/7

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

1	
Ethane (74-84-0)	
Log Pow	<= 2.8

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations

Additional Information: Handle empty containers with care because residual vapors are flammable. Disposal through controlled incineration, flare, or authorized waste dump.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name : NATURAL GAS, COMPRESSED (with high methane content)

Hazard Class : 2.1 Identification Number : UN1971 Label Codes : 2.1

ERG Number : 115
14.2. In Accordance with IMDG

Proper Shipping Name : NATURAL GAS, COMPRESSED

Hazard Class : 2.1
Identification Number : UN1971
Label Codes : 2.1
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
14.3. In Accordance with IATA

Proper Shipping Name : NATURAL GAS, COMPRESSED

Identification Number: 2.1Hazard Class: UN1971Label Codes: 2.1ERG Code (IATA): 10L





Proper Shipping Name : NATURAL GAS, COMPRESSED with high methane content

Hazard Class : 2.1 Identification Number : UN1971 Label Codes : 2.1



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Natural Gas Compressed		
SARA Section 311/312 Hazard Classes	Fire hazard	
	Sudden release of pressure hazard	
	Immediate (acute) health hazard	

Methane (74-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Ethane (74-84-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

05/09/2016 EN (English US) 6/7

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

15.2. US State Regulations

Methane (74-82-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Ethane (74-84-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

15.3. Canadian Regulations

	Methane (7
Listed on the Canadian DSL (Domestic Substances List)	Listed on th

Ethane (74-84-0)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 11/20/2018

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR).

GHS Full Text Phrases:

Compressed gas	Gases under pressure Compressed gas
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
	May displace oxygen and cause rapid suffocation

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015

05/09/2016 EN (English US) 7/7